



US005741120A

United States Patent [19]

Bass et al.

[11] Patent Number: 5,741,120

[45] Date of Patent: Apr. 21, 1998

[54] **CAPACITY MODULATED SCROLL MACHINE**

[73] Inventors: Mark Bass, Sidney; Roy J. Doepker, Lima; Jean-Luc M. Caillat, Dayton; Wayne R. Warner, Piqua, all of Ohio

[73] Assignee: Copeland Corporation, Sidney, Ohio

[21] Appl. No.: 486,118

[22] Filed: Jun. 7, 1995

[51] Int. Cl.⁶ F04B 49/00

[52] U.S. Cl. 417/44.2; 417/214; 418/55.5

[58] Field of Search 418/55.5, 57; 417/212, 417/214, 44.11, 44.2

References Cited**U.S. PATENT DOCUMENTS**

4,505,651	3/1985	Terauchi et al.	417/440
4,575,318	3/1986	Blain .	
4,610,610	9/1986	Blain .	
4,774,816	10/1988	Uchikawa et al.	418/15
4,846,633	7/1989	Suzuki et al.	417/310
5,263,822	11/1993	Fujio .	418/55.5
5,290,161	3/1994	Swain .	
5,336,058	8/1994	Yokoyama .	417/299
5,342,185	8/1994	Anderson .	418/55.5
5,342,186	8/1994	Swain .	418/57
5,411,384	5/1995	Bass et al.	418/55.5
5,435,707	7/1995	Hirano et al.	418/55.5

FOREIGN PATENT DOCUMENTS

59-117895 8/1984 Japan .

Primary Examiner—Timothy Thorpe
Assistant Examiner—Peter G. Korytnyk
Attorney, Agent, or Firm—Harness, Dickey & Pierce, P.L.C.

[57] **ABSTRACT**

A scroll-type machine is disclosed which is particularly well suited for use as a compressor in refrigeration and air conditioning systems and incorporates a unique arrangement for modulating the capacity thereof. In one group of embodiments the capacity of the scroll-type machine is modulated by relative axial movement between the scroll members so as to form a leakage path across the wrap tips and opposed end plates. In another group of embodiments, modulation is achieved by reducing the orbital radius of one of the scroll members to thereby form a leakage path across the flank surfaces of the wraps. Both types of scroll separation may be accomplished in a time pulsed manner to thereby enable a full range of modulation with the duration of the loading and unloading periods being selected to maximize the efficiency of the overall system. A motor control arrangement is also disclosed which may be used with either of the modulation methods mentioned above to increase the efficiency of the motor during periods of reduced load. Additionally, either of the modulation arrangements mentioned above may be combined with a delayed suction form of capacity modulation with or without the motor control feature to thereby achieve better operating efficiency under certain conditions.

102 Claims, 28 Drawing Sheets